



# STRIKE C

115

Stage V



TECHNICAL DATA		STRIKE C	
		115	
ENGINE			
Model			FARMotion 45
Emission level			Stage V
Cylinders/Displacement	n°/cc		4/3849
Bore/Stroke	mm		103/115.5
Turbo Intercooler			■
Common Rail injection	bar		2000
Max. power (ECE R120)	kW/HP		85/116
Power at rated engine speed (ECE R120)	kW/HP		80.6/110
Max. torque	Nm		472
Engine speed at maximum torque	rpm		1400
Electronic engine control			■
PowerCore air filter			■
Fuel tank capacity	l		130
AdBlue tank capacity	l		11
EAT	System		DOC+DPF+SCR
TRANSMISSION			
SDF transmission			CT4150
Gearbox			4 gears x 2 ranges x OverDrive or 4 gears x 3 ranges
Shuttle	Type		Mechanical
N°of speeds (OverDrive)	n°		16+16
N°of speeds (creeper)	n°		12+12
PTO			
Electrohydraulic engagement			■
540/540ECO			■
540/1000			□
LIFT			
Mechanical rear lift			■
Rear lift capacity	kg		3170
HYDRAULICS			
Pump flow	l/min		50+25
Rear spool valves (STD)	n°		3
Rear spool valves (OPT)	n°		5
BRAKES AND STEERING			
Multi-plate wet lateral steering clutches			■
Wet band steering brakes			■
Pedal operated service brake			■
TRACKS			
Number of rollers	n°		6
Manual chain tightener			■
Track type			Steel
Number of shoes	n°		40
Shoe width	mm		450
Dry chains			■
Lubricated chains			□
DRIVING STATION			
Flat floor platform suspended on Silent-Block			■
4-post safety frame			■
Sun roof canopy			□
Driving seat with mechanical suspension			■
Driving seat with pneumatic suspension			□
2+2 Halogen working lights on roof			□
2+2 LED working lights on roof			□
Aftermarket cab prearrangement			□
DIMENSIONS AND WEIGHTS - WITH STEEL TRACKS			
Shoe width	mm		450
Wheelbase	mm		1850
Max. length	mm		3550
Total height	mm		2320
Width	mm		1800
Unladen weight	kg		5350

STD ■ OPT □ Not available -

www.lamborghini-tractors.com



Lamborghini Trattori is a brand of SDF

