

Lamborghini

Cross 55 S



- 1000.3 Series SDF, Tier1 with 3 cylinders
- 540 PTO transmission
- Available in 2WD and 4WD version

- 30 km/h max. speed
- 12 FWD + 3 REV with mechanically operated gearbox
- Compact and essential


CROSS S
55 | 65



TECHNICAL DATA		CROSS S	
		55	65
ENGINE			
Emissions		Tier1	Tier1
Manufacturer		SDF 1000.3	SDF 1000.3
Cylinders/Capacity	No./cm ³	3/3,000	3/3,000
Natural aspiration		●	●
Max. homologated power (ECE R 120)	kW/HP	37/50	44/60
Max. engine speed (rated)	rpm	2,350	2,350
Max. torque	Nm	175	195
Mechanical engine control		●	●
Cyclone prefilter		●	●
Cooling liquid		●	●
Under-hood silencer with vertical exhaust		●	●
Fuel tank capacity	litres	56	56
MECHANICAL GEARBOX			
Synchronised		●	●
Number of speeds	n°	8+2	8+2
Number of speeds with reduction gear	n°	12+3	12+3
Minimum/maximum speed with reduction gear	km/h	0.81/2.91	0.83/2.95
Max. speed	km/h	33	34.5
Mechanical dry clutch, single		●	●
REAR PTO			
Mechanical dry clutch, single		●	●
Mechanical engagement		●	●
PTO 540		●	●
FRONT AND REAR AXLE			
Four wheel drive mechanically engaged (only 4WD versions)		●	●
Mechanically operated differential lock		●	●
Steering angle/turning circle 2WD	degrees/mm	50°/ 3,550	50°/3,550
Steering angle/turning circle 4WD	degrees/mm	55°/ 3,700	55°/3,700
BRAKES			
Braking system with wet brake discs		●	●
Mechanical parking brake		●	●
STEERING			
Hydrostatic steering with independent pump		●	●
HITCH			
Category		II	II
Rear hitch mechanical		●	●
Rear hitch lift capacity	kg	1,500	1,500
HYDRAULIC SYSTEM			
Pump output (std)	L/min	31	31
Open-centre hydraulic system		●	●
Mechanical valve engagement		●	●
Rear hydraulic auxiliary valves	No. of ways	2/4	2/4
DRIVING POSITION			
Side control levers		●	●
ROPS with two uprights		○	○
Driver seat with mechanical suspension		●	●
Analogue instrumentation		●	●
DIMENSIONS AND WEIGHTS			
Standard rear tyres		14.9R28"	16.9R28"
Max. length	mm	3,470	3,470
Width (min-max)	mm	1,685-2,125	1,822-2,336
Wheelbase (4WD/2WD)	mm	1,975-2,045	1,975-2,045
Front track (4WD/2WD)	mm	1,455-1,250	1,480-1,335
Rear track	mm	1,340	1,410
Max. weight at steering	mm	1,550	1,575
Max. height at cowl	mm	1,355	1,370
Weight with ROPS (4WD/2WD)	kg	2,150/1,940	2,300/2,090

STD ● OPT ○

DEALER

Discover more at lamborghini-tractors.com
 The use of original lubricants and coolants is recommended.
 Lamborghini Trattori is a brand of  SDF



Technical data and pictures are guideline only. Lamborghini Trattori is committed to delivering a product that best suits your needs, and reserves the right to modify its products at any time without prior notice. Produced by Marketing Department - Code 308.8174.3.2-5 10/2016